

OPTICORE JT3-2-6.3 x L range

A2 stainless steel bi-met fastener for membrane faced sandwich panel side laps.

Application Features



- Engineered integral nylon head for rapid coring of the membrane and insulation core for a one step fix of membrane faced sandwich panels
- Laps stitching of membrane faced sandwich panels
- Stitching 2 x 0.5mm - 2 x 1.0mm

Material Specification


- High quality stainless steel grade A2 to ISO 3506, EN 1.4301 to ISO 10088, AISI 304
- Hardened carbon steel drill point and lead threads
- High impact resistant coloured nylon head. Resistant to temperatures from -40°C to 120°C

**Performance Details****Ultimate Fastener Tensile Strength**


| Fastener Diameter | kN |
|-------------------|-------|
| 6.3 x L | 15.70 |

**Ultimate Fastener Shear Strength**

| Fastener Diameter | kN |
|-------------------|-------|
| 6.3 x L | 10.20 |

**Ultimate Pullout Load kN**

| Fastener Diameter | 0.70 | 0.90 |
|-------------------|------|------|
| 6.3 x L | 1.36 | 2.50 |




Figures based on tests from construction grade steel designated as S220GD (BS EN 10346), minimum yield strength 220 N/mm².

Ultimate Pullover Load kN

| Washer Face | Nominal Steel Thickness (mm) | |
|-------------|------------------------------|------|
| | 0.63 | 0.50 |
| Unwashed | 5.70 | 3.50 |

Figures based on use with Kingspan Topdek profile steel sheets with fastener located in valley of profile.



Figures shown on this data sheet are based on results obtained from tests carried out in EJOT UK's Applitec laboratory in accordance with equipment conforming to current industry standards, on a random sample of fasteners manufactured to EJOT tolerances. Information supplied should form part of a general guide and should performance data for a specific application be required please do not hesitate to contact us.