

HERCULES DECKING - FIXED HEAD




INDEX

1. Code registry
2. Description
3. Use
4. Carrying capacity
5. Fields of use
6. Technical specification


1. CODE REGISTRY

Code	Description	Dimensions (mm)	Weight	Pkg / Pallet
TER09-1183/1F25	Fixed Head Hercules for 4 mm joint	from 25 to 37	0,22	30 pcs. / 720 pcs.
TER09-1183/1F37	Fixed Head Hercules for 4 mm joint	from 37 to 60	0,28	30 pcs. / 480 pcs.
TER09-1183/1F60	Fixed Head Hercules for 4 mm joint	from 60 to 94	0,40	25 pcs. / 300 pcs.
TER09-1183/1F94	Fixed Head Hercules for 4 mm joint	from 94 to 150	0,54	20 pcs. / 160 pcs.
TER09-1183/1F150	Fixed Head Hercules for 4 mm joint	from 150 to 270	0,73	15 pcs. / 120 pcs.
TER09-1183/PI20	Extension only for Hercules 150 - 270	h. 120	0,18	20 pcs. / 300 pcs.
TER09-1283CHI	Adjustment key for Hercules	-	0,20	1 pcs. / -


MATERIAL Made of PP (polypropylene).



TER09-1183/1F25




TER09-1183/1F37




TER09-1183/1F60


HERCULES DECKING - FIXED HEAD




TER09-1183/1F94



TER09-1183/1F150



BACK BASE



FIXED HEAD

2. DESCRIPTION

Hercules adjustable support for outdoor flooring, with adjustable height from min. 25 to max. 390 mm (depending on the model used). Each pack contains the complete disassembled support with base, screw and fixed head for decking for fixing the joist. The head of the holder is equipped with integrated anti-noise rubber. Only the model from h. 150 to 270 mm can be extended by applying the specific extension h. 120 mm (TER09-1183 / P120). The finalization of the adjustment of the support takes place with the floor installed using the appropriate key.

3. USE

Used in external areas, terraces, pavements.
The use of polishing and sanding machines is not recommended.

4. CARRYING CAPACITY

- Minimum load capacity = 15 kN (totally extended)
- Maximum load capacity = 30 kN (completely not extended)


5. FIELDS OF USE

Waterproof membrane, hard insulating panels, squids and solid and compact pose plans

HERCULES DECKING - FIXED HEAD



TER09-1183/P120



TER09-1183/CHI

6. TECHNICAL SPECIFICATION

Code	Description	Unit	Price
Dak.D.TER09.1183/1Fxxx	Supply and installation of adjustable support with fixed head "Hercules", for external decking. Dimensions from min. 25 to max. 390 mm (depending on the model used). Available in black colour Made of polypropylene Used in external areas, terraces, pavements.	pc.	-
Dak.D.TER09.1183/1F25	Hercules with adjustable height from 25 to 37 mm and base diameter of 210mm.....	pc.	-
Dak.D.TER09.1183/1F37	Hercules with adjustable height from 37 to 60 mm and base diameter of 210mm.....	pc.	-
Dak.D.TER09.1183/1F60	Hercules with adjustable height from 60 a 94 mm and base diameter of 230mm.....	pc.	-
Dak.D.TER09.1183/1F94	Hercules with adjustable height from 94 a 150 mm and base diameter of 230mm.....	pc.	-
Dak.D.TER09.1183/1F150	Hercules with adjustable height from 150 a 270 mm and base diameter of 230mm.....	pc.	-
Dak.D.TER09.1183/P120	Extension h.120mm in polypropylene compatible with Hercules support 150, TER09-1183/1F150	pc.	-
Dak.D.TER09.1283	Adjustment key for Hercules	pc.	-